

Package: FPCA3D (via r-universe)

October 11, 2024

Type Package

Title Three Dimensional Functional Component Analysis

Version 1.0

Date 2018-07-09

Author Nan Lin, Momiao Xiong

Maintainer Nan Lin <edmondlinnan@gmail.com>

Description Run three dimensional functional principal component analysis and return the three dimensional functional principal component scores. The details of the method are explained in Lin et al.(2015) <[doi:10.1371/journal.pone.0132945](https://doi.org/10.1371/journal.pone.0132945)>.

License GPL-2 | GPL-3

Depends graphics, grDevices, stats, utils

NeedsCompilation no

Date/Publication 2018-07-10 15:20:09 UTC

Repository <https://edmondlinnan.r-universe.dev>

RemoteUrl <https://github.com/cran/FPCA3D>

RemoteRef HEAD

RemoteSha ec740cf7237ec19b5fda370772e15d5801d39042

Contents

FPCA3D-package	2
FFT2FS_3D	3
FPCA_3D_score	4

Index	5
--------------	----------

FPCA3D-package

Three Dimensional Functional Component Analysis

Description

Run three dimensional functional principal component analysis and return the three dimensional functional principal component scores. The details of the method are explained in Lin et al.(2015) <doi:10.1371/journal.pone.0132945>.

Details

The DESCRIPTION file:

```
Package:      FPCA3D
Type:         Package
Title:        Three Dimensional Functional Component Analysis
Version:      1.0
Date:         2018-07-09
Author:       Nan Lin, Momiao Xiong
Maintainer:   Nan Lin <edmondlinnan@gmail.com>
Description:  Run three dimensional functional principal component analysis and return the three dimensional functional principal component scores.
License:      GPL-2|GPL-3
Depends:      graphics, grDevices, stats, utils
```

Index of help topics:

```
FFT2FS_3D          Three dimensional Fourier Series
FPCA3D-package     Three Dimensional Functional Component Analysis
FPCA_3D_score      Three Dimensional Functional Component Analysis
```

```
data_in = array(runif(4000,0,1),dim=c(10,10,10,4)) test = FPCA_3D_score(data_in,0.8)
```

Author(s)

Nan Lin, Momiao Xiong

Maintainer: Nan Lin <edmondlinnan@gmail.com>

References

Lin N, Jiang J, Guo S, Xiong M. Functional Principal Component Analysis and Randomized Sparse Clustering Algorithm for Medical Image Analysis. PLOS ONE. 2015;10(7):e0132945.

See Also

[FFT2FS_3D](#), [FPCA_3D_score](#)

Examples

```
data_in = array(runif(4000,0,1),dim=c(10,10,10,4))
test = FPCA_3D_score(data_in,0.8)
```

FFT2FS_3D*Three dimensional Fourier Series*

Description

Calculate the three dimensional Fourier series coefficients of the input three dimensional array.

Usage

```
FFT2FS_3D(A)
```

Arguments

A A three dimensional numerical data array. For example, *A* can be the data array of an three dimensional image.

Details

Calculate the three dimensional numerical data array. The input *A* array can be any three dimensional data array. For image input data, the input should be data array only without any header information.

Value

A three dimensional Fourier series coefficients array of the input *A* data array.

References

Lin N, Jiang J, Guo S, Xiong M. Functional Principal Component Analysis and Randomized Sparse Clustering Algorithm for Medical Image Analysis. PLOS ONE. 2015;10(7):e0132945.

Examples

```
test_data = array(runif(1000,0,1),dim = c(10,10,10))
r1t = FFT2FS_3D(test_data)
```

FPCA_3D_score

Three Dimensional Functional Component Analysis

Description

Calculation of three dimensional functional principal component scores for a series of three dimensional array data.

Usage

```
FPCA_3D_score(X, prop)
```

Arguments

<code>X</code>	The input data array. X is a four dimensional data array. The first three dimensional data represents the three dimensional data array for each observation. The fourth dimension represents the observations.
<code>prop</code>	The prespecified proportion of variance the calculated functional principal component scores can explain in the functional domain.

Details

Calculate the three dimensional functional principal component scores for a series of three dimensional data.

Value

A two dimensional score matrix. The row of the score matrix represents each individual and the column of the score matrix represent each component score.

References

Lin N, Jiang J, Guo S, Xiong M. Functional Principal Component Analysis and Randomized Sparse Clustering Algorithm for Medical Image Analysis. PLOS ONE. 2015;10(7):e0132945.

Examples

```
data_in = array(runif(4000,0,1),dim=c(10,10,10,4))
test = FPCA_3D_score(data_in,0.8)
```

Index

* **package**

FPCA3D-package, [2](#)

FFT2FS_3D, [2](#), [3](#)

FPCA3D (FPCA3D-package), [2](#)

FPCA3D-package, [2](#)

FPCA_3D_score, [2](#), [4](#)